

■ ELECTRICAL SPECIFICATION



PARAMETER		VALUE				UNIT
Frequency Range		698~960	1710~2170	2500~2700	3500~4000	MHz
Gain		7	10			dBi
F/B Ratio, min		15 / 20				dB
Horizontal Beam width		70 / 75				°
Vertical Beam width		75 / 60				°
VSWR, max		1.5				-
Radiation		Direction				-
Polarization		Vertical and Horizontal				-
Lightning Protection		DC Grounded				-
Input Power, max		50				W
Impedance		50				Ω
Connector		2xN Female				-
Antenna Radome Material		ABS				-
Mounting Way		Pole				-
Diameter of Installation Pole		Ø30 ~ Ø50				mm
Dimensions		340 x 225 x 60				mm
Cable	Type	RG58U				-
	Length	300				mm
Weight		1.1				kg
Operating Temperature Range		-40 ~ +60				°C
RoHS Compliant		YES				-



Raltron Electronics / RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided only for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.

Copyright © 2016, Raltron Electronics / RAMI Technology USA, LLC. All rights reserved. No part of this document may be reproduced in any form without the prior written permission of Raltron Electronics / RAMI Technology USA, LLC.

March 2021