



■ SPECIFICATION

PARAMETERS		VALUE	UNIT
Frequency Range		915	MHz
Gain		2.15	dBi
VSWR, max		2.0	-
Polarization		Vertical	-
Input Power, max		50	W
Impedance		50	Ω
Connector		IPEX	-
Cable	Type	1.13	mm
	Length	10	cm
Antenna Radome Material		FPC	-
Dimensions		33 x 8 x 0.2	mm
Weight		5	g
Operating Temperature Range		-40 ~ 70	$^{\circ}\text{C}$
RoHS Compliant		YES	-

■ APPROVAL

RALTRON	
DRAWN BY:	AR, March 29, 2019
APPROVED BY:	CP, March 29, 2019
REVISION:	A, Initial Release

Raltron Electronics/RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort to ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.

Copyright © 2016, Raltron Electronics / RAMI Technology USA, LLC. All rights reserved. No part of this document may be reproduced in any form without the prior written permission of Raltron Electronics / RAMI Technology USA, LLC.