



● ELECTRICAL SPECIFICATIONS

PARAMETER		VALUE
NOMINAL FREQUENCY		4.000 MHz
FREQUENCY TOLERANCE AT 25°C, MAX		±0.5%
FREQUENCY STABILITY OVER TEMPERATURE, MAX		±0.3%
OPERATING TEMPERATURE RANGE		-25°C TO +85°C
AGING OVER 10 YEARS, MAX		±0.3%
RESONANT IMPEDANCE, MAX		30 Ω
BUILT IN CAPACITANCE (C1=C2), ±20%		33 pF
WITHSTANDING VOLTAGE (DC, 1 MAX)		50 V
INSULATION RESISTANCE, MIN		500 MΩ
INPUT VOLTAGE	DC VOLTAGE	6 V
	AC VOLTAGE (PEAK TO PEAK)	15 V
STORAGE TEMPERATURE		-55°C TO +85°C

● MECHANICAL SPECIFICATION



REFLOW PROFILE



Reflow profile		
Temperature Min Preheat	T_{SMIN}	140°C
Temperature Max Preheat	T_{SMAX}	160°C
Time (T_{SMIN} to T_{SMAX})	t_s	80-120 sec.
Temperature	T_L	200°C
Peak Temperature	T_P	230°C max
Ramp-up rate	R_{UP}	3°C/sec max.
Ramp-down rate	R_{DOWN}	6°C/sec max.
Time within 5°C of Peak Temperature	t_p	10 sec.
Time $t[25^\circ\text{C}]$ to Peak Temperature	$t[25^\circ\text{C}]$ to Peak	130 sec.
Time	t_L	20-40 sec.

ENVIRONMENTAL

PARAMETER	VALUE
MOISTURE SENSITIVITY LEVEL	1
RoHS-2	5/6 COMPLIANT, exemption 7c
REACH SVHC	COMPLIANT
HALOGEN-FREE	COMPLIANT
ESD CLASSIFICATION LEVEL	N/A
TERMINATION FINISH	Sn



APPROVAL

DRAWN BY:	KJackson, April 13, 2016
APPROVED BY:	KJackson, April 13, 2016
REVISION:	A, Initial Release



A **RAMI TECHNOLOGY** Company

SURFACE MOUNT CERAMIC RESONATOR

Page 3 of 3

SMR-4.000-B

Raltron Electronics/RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort to ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.