


#### ELECTRICAL SPECIFICATION


PARAMETER	SYMBOL	CONDITIONS	VALUE	UNIT
Nominal Frequency	$f_o$	Ta=25°C	12.000	MHz
Supply Voltage Range	V <sub>CC</sub>	---	3.3V	VDC
Supply Current, max	I <sub>s</sub>	Ta=25°C	10	mA
Operating Temperature Range	Ta	---	-40 ~ +85	°C
Storage Temperature Range	T(stg)	Absolute max	-55 ~ +125	°C
Frequency Tolerance	$\Delta f/f_o$	Inclusive of 25°C Tolerance and Changes due to Operating Temperature, Supply Voltage, Load, Aging, Shock and Vibration	±50	ppm
Output Voltage	V <sub>OL</sub>	Logic "0" Level	0.1 x V <sub>CC</sub>	VDC
	V <sub>OH</sub>	Logic "1" Level	0.9 x V <sub>CC</sub>	VDC
Output Load	---	CMOS Output	15	pF
Enable / Disable Function	E/D	Pin 1: High, Pin 3 – Oscillation (Enabled), min	0.7 x V <sub>CC</sub>	V
		Pin 1: Low, Pin 3 – High Impedance (Disabled), max	0.3 x V <sub>CC</sub>	V
Symmetry (Duty Cycle)	DC	@50% V <sub>DD</sub>	45 to 55	%
Rise Time and Fall Time	t <sub>r</sub> / t <sub>f</sub>	@10% to 90% V <sub>DD</sub>	20	ns
Stand-by Current	I(std)	---	10	μA
Start up time, max	t <sub>s</sub>	V <sub>OUT</sub> ≥ 90% V <sub>P.P</sub>	5	ms
Phase Jitter, RMS ,max	J	@ 12kHz < F <sub>j</sub> < 20MHz	1.0	ps

#### MECHANICAL SPECIFICATION



NOTE: A capacitor of 0.01 μF between V<sub>CC</sub> and Ground is recommended

#### REFLOW PROFILE



Reflow profile			
Temperature Min Preheat	$T_{SMIN}$		150°C
Temperature Max Preheat	$T_{SMAX}$		200°C
Time ( $T_{SMIN}$ to $T_{SMAX}$ )	$t_s$		60-180 sec.
Temperature	$T_L$		217°C
Peak Temperature	$T_P$		260°C
Ramp-up rate	$R_{UP}$		3°C/sec max.
Ramp-down rate	$R_{DOWN}$		6°C/sec max.
Time within 5°C of Peak Temperature	$t_P$		10 sec.
Time $t[25^\circ\text{C}]$ to Peak Temperature	$t[25^\circ\text{C}]$ to Peak		480 sec.
Time	$t_L$		60-150 sec.

#### ENVIRONMENTAL

PARAMETER	VALUE
MOISTURE SENSITIVITY LEVEL	1
RoHS	Compliant
REACH-SVHC	Compliant
HALOGEN-FREE	Compliant
TERMINATION FINISH	Au





A RAMI TECHNOLOGY Company

# CLOCK OSCILLATOR

Page 3 of 3

## COM1305-12.000-EXT-T-TR

### MARKING

Rx12.0  
•3BEyw

x – Internal Production ID code  
y – Year code  
w – Week code

YEAR CODE	
Year	Code
2019	9
2020	0
2021	1
2022	2
2023	3
2024	4
2025	5
2026	6
2027	7
2028	8
2029	9

ALPHA WEEK CODE TABLE					
Week	Code	Week	Code	Week	Code
1	a	19	s	37	K
2	b	20	t	38	L
3	c	21	u	39	M
4	d	22	v	40	N
5	e	23	w	41	O
6	f	24	x	42	P
7	g	25	y	43	Q
8	h	26	z	44	R
9	i	27	A	45	S
10	j	28	B	46	T
11	k	29	C	47	U
12	l	30	D	48	V
13	m	31	E	49	W
14	n	32	F	50	X
15	o	33	G	51	Y
16	p	34	H	52	Z
17	q	35	I		
18	r	36	J		

### APPROVAL

RALTRON	
DRAWN BY:	KJackson, January 27, 2016
APPROVED BY:	KJackson, January 27, 2016
REVISION:	A, Initial Release
	B, AR, May 18, 2022
	Updated to the current specs level

Raltron Electronics/RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort to ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.

Copyright © 2016, Raltron Electronics / RAMI Technology USA, LLC. All rights reserved. No part of this document may be reproduced in any form without the prior written permission of Raltron Electronics / RAMI Technology USA, LLC.