

OCXO SERIES OXD30

FEATURES

Ultra High Stability
Low Aging



ELECTRICAL SPECIFICATIONS

PARAMETER	SYMBOL	CONDITION	VALUE			UNIT
			Min.	Typ.	Max.	
Frequency Range*	f_0			10.000		MHz
Supply Voltage	V_s	$V_s \pm 5\%$	3.135	3.3	3.465	V
			4.75	5.0	5.25	
			11.40	12.0	12.60	
Power Consumption	P_s	Steady state, @ 25°C			2.0	W
	P_{sw}	During warm-up, @ 25°C			4.7	W
Warm-up Time	t_w	V_s , $T_a = +25^\circ\text{C}$, within ± 100 ppb of final frequency with reference after 1 hour on			5	min
Frequency Calibration	$\Delta f/f_0$	$T_a = +25^\circ\text{C}$, after 15mins power on ref. to nominal frequency	-100		+100	ppb
Frequency Stability vs. Temperature	$\Delta f/f_0 (T_a)$	Measurement referenced to $(f_{max} + f_{min})/2$. See Table	-0.2		+0.2	ppb
Frequency Stability vs. Supply Voltage	$\Delta f/f_0 (\Delta V_{CC})$	$T_a = 25^\circ\text{C}$, $V_s \pm 5\%$, load = 15pF	-0.3		+0.3	ppb
Frequency Stability vs. Load Variation	$\Delta f/f_0 (\Delta I)$	$T_a = 25^\circ\text{C}$, V_s , load = 15pF $\pm 5\%$	-0.3		+0.3	ppb
Aging, after 30 days of operation	$\Delta f/\Delta t_d$	Per day	-0.2		+0.2	ppb
	$\Delta f/\Delta t_y$	First year	-50		+50	ppb
	$\Delta f/\Delta t_y$	10 years	-0.3		+0.3	ppm
Operating Temperature Range			-40		+80	°C
Storage Temperature	$T_{(stg)}$		-40		+105	°C
Short Term Stability		$\tau = 1s$			0.05	ppb
Control Voltage Range	V_c		0	2.5	5.0	V
Frequency Tuning Range		$V_c = 0V$	-0.8		-0.4	ppm
		$V_c = 1.65V$	-200		+200	ppb
		$V_c = 3.3V$	+0.4		+0.8	ppm
Linearity			-10		+10	%

*Not any Combination Frequency-Operating Temperature Range- Stability is available. Please consult factory

**The above Specification is an example for 10.000MHz, 5V

OCXO SERIES OXD30

PHASE NOISE

PARAMETER	SYMBOL	CONDITION	VALUE			UNIT
			Min.	Typ.	Max.	
@1 Hz Offset	$\mathcal{E} (\Delta f)$				-90	dBc/Hz
@10 Hz Offset	$\mathcal{E} (\Delta f)$				-120	dBc/Hz
@100 Hz Offset	$\mathcal{E} (\Delta f)$				-140	dBc/Hz
@1 kHz Offset	$\mathcal{E} (\Delta f)$				-145	dBc/Hz
@10 kHz Offset	$\mathcal{E} (\Delta f)$				-150	dBc/Hz
@100 kHz Offset	$\mathcal{E} (\Delta f)$				-155	dBc/Hz

CMOS OUTPUT CHARACTERISTICS

PARAMETER	SYMBOL	CONDITION	VALUE			UNIT
			Min.	Typ.	Max.	
Output Levels	V_{OH}/V_{OL}	$V_{CC} = 5.0V, \text{load} = 15pF$		3.8/0.5		V
Duty Cycle	DC	load = 15pF		45/55		%
Rise/Fall Time	t_r/t_f	10% ~ 90% V_{out}			5	ns
Load				15		pF

SINE-WAVE OUTPUT CHARACTERISTICS


PARAMETER	SYMBOL	CONDITION	VALUE			UNIT
			Min.	Typ.	Max.	
Output Levels			5	7	9	dBm
Harmonics					-40	dBc
Spurious					-70	dBc
Load				50		Ω

OCXO SERIES OXD30

ENVIRONMENTAL MECHANICAL CONDITIONS

Storage Temperature Range	-55°C to +105°C
Drop Test	The test shall be carried out as the provisions of the IEC60028-2-32 test Ed. 10cm height, 3 times on hard board with thickness of 3cm
Bumping Test	Device are bumped to three mutually perpendicular axes at peak acceleration of 400m/s ² , each 4000±10times, 6ms pulse duration time
Vibration Test	Frequency range: 1Hz-4Hz-100Hz-200Hz Acceleration: 0.0001g ² /Hz-0.01g ² /Hz-0.01g ² /Hz-0.001g ² /Hz Grms=1.15g Sweep time: 30 minutes (perpendicular axes each sweep time)
Mechanical Shock	100g, 6mS duration, 1/2 sine wave, 3 shocks each direction along 3 mutually perpendicular planes.
Thermal shock	0.5h@-40°C, 0.5h@+85°C, Note: the changing time < 30 seconds, cycling for 100 times

MECHANICAL DIMENSIONS AND PIN FUNCTIONING



H = 0.59"/15mm max

PIN	SYMBOL	FUNCTION
1	N/C or V _c	No connect or Control Voltage
2	N/C or V _{ref}	No connect or Reference Voltage
3	V _s	Supply Voltage
4	OUTPUT	RF Output
5	GND	Case/Ground

OCXO SERIES OXD30

■ PART NUMBERING SYSTEM

Prefix	Output Type	Control Voltage	Series	Revision	Temperature Range	Stability	Frequency	Supply Voltage
OXD	4: LVCMOS 6: SINE	1: No Control Voltage 5: Control Voltage	30:3000	A	First letter: Lowest Temperature, Second letter: Highest Temperature: From A=-55°C to Z=+70°C, Then: 1=+75°C, 2=+80°C, 3=+85°C... in 5°C Steps Example: HZ: -20°C to +70°C LZ: 0°C to +70°C D3: -40°C to +85°C	Value x 10E-2in ppm Example: 1 = 0.01 ppm=10 ppb 0.1 = 0.001 ppm = 1ppb 0.01 = 0.0001 ppm = 0.1ppb 0.02= 0.0002 ppm =0.2ppb	10.000	3: 3.3 V 5: 5.0 V 12: 12.0 V

OXD 4 5 30 A-D3-0.02-20.000- 5



Supply Voltage: 5 V

Frequency: 20 MHz

Temp Stability: 0.02 x 10E -2 = ±0.2 ppb

Operating Temp Range: -40° C to 85°C

Revision: "A"

SERIES: 3000

Electrical Control Voltage

Output: LVCMOS

Prefix: OCXO

May , 2022

Raltron Electronics/RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort to ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.