


RSF-169.200-128-7050-TR-49

page 1 of 3


Items		Specification	Unit
Center frequency(Fo)		169.200	MHz
Bandwidth @-3dB, typ		128	kHz
Bandwidth @-10dB, typ/max		183 / 200	kHz
Insertion Loss (within F ₀ -7.5~F ₀ +30.4kHz) typ / max		2.6 / 3.6	dB
Ripple in Pass Band (within F ₀ -7.5~F ₀ +30.4kHz) typ/max		0.6 / 1.0	dB
Attenuation	159.200 ~ 168.280 MHz, min/typ	-50 / -54	dB
	170.120 ~ 183.075 MHz, min/typ	-45 / -52	dB
Aging, max		±10	ppm/year
Input power, max		20	dBm
DC Voltage, max		10	V
Operating Temperature		-40 to +85	°C
Storage Temperature		-40 to +85	°C

Dimension




Pin Description	
A,B,C,F,G,H	Ground
I	Ground
J	Input
D	Ground
E	Output

Frequency Characteristics



● **REFLOW PROFILE**



Reflow profile		
Temperature Min Preheat	T_{SMIN}	150°C
Temperature Max Preheat	T_{SMAX}	200°C
Time (T_{SMIN} to T_{SMAX})	t_s	60-180 sec.
Temperature	T_L	217°C
Peak Temperature	T_P	260°C
Ramp-up rate	R_{UP}	3°C/sec max.
Ramp-down rate	R_{DOWN}	6°C/sec max.
Time within 5°C of Peak Temperature	t_p	10 sec.
Time $t[25^\circ\text{C}]$ to Peak Temperature	$t[25^\circ\text{C}]$ to Peak	480 sec.
Time	t_L	60-150 sec.

● **ENVIRONMENTAL**

PARAMETER	VALUE
MOISTURE SENSITIVITY LEVEL	1
RoHS-2	6/6 COMPLIANT & LEAD FREE
REACH SVHC	COMPLIANT
HALOGEN-FREE	COMPLIANT
ESD CLASSIFICATION LEVEL	N/A
TERMINATION FINISH	Au



April 2016