


ELECTRICAL SPECIFICATION

PARAMETER	VALUE	UNIT	
Frequency Range	4900 ~ 5900	MHz	
Gain	6	dBi	
VSWR, typ/max	1.5 / 1.8	-	
H Plane BW	360	°	
E Plane BW	20 ±2	°	
Polarization	Vertical	-	
Input Power, max	10	W	
Impedance	50	Ω	
Connector	N Male	-	
Radome Material	ABS	-	
Radome Color	White	-	
Dimensions	∅22 x 200	mm	
Weight	250±50	g	
IP Rating	IP65	-	
Humidity	No Condensation	95	%
Operating Temperature Range	-30 ~ +70	°C	
Storage Temperature Range	-40 ~ +85	°C	



FREQUENCY CHARACTERISTICS



Raltron Electronics / RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided only for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.

Copyright © 2016, Raltron Electronics / RAMI Technology USA, LLC. All rights reserved. No part of this document may be reproduced in any form without the prior written permission of Raltron Electronics / RAMI Technology USA, LLC.

December 2020