

ELECTRICAL SPECIFICATION

SPECIFICATIONS		SPECIFICATIONS		UNIT
Frequency Range		800 ~ 960	1710 ~ 2500	MHz
Gain		3	5	dBi
Nominal Impedance		50		Ω
VSWR, max		1.5		-
Polarization		Vertical		-
Power, max		100		W
Dimensions	Diameter	170		mm
	Height	72		mm
Weight		300		g
Connector		SMA Male		-



APPROVAL

RALTRON	
DRAWN BY:	LP, November 29, 2016
APPROVED BY:	CP, November 29, 2016
REVISION:	A, Initial Release

Raltron Electronics/RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort to ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.

Copyright © 2016, Raltron Electronics / RAMI Technology USA, LLC. All rights reserved. No part of this document may be reproduced in any form without the prior written permission of Raltron Electronics / RAMI Technology USA, LLC.