

# **GSM ANTENNA**

Page 1 of 1

## RPA-GS-P-47-UFL-100-A

#### ELECTRICAL SPECIFICATION

SPECIFICATIONS	SPECIFICATIONS	UNIT
Frequency Range	900 / 1800	MHz
Gain	2.15	dBi
VSWR, max	2.0	-
Radiation	Omni	-
Polarization	Vertical	-
Input Power, max	50	W
Impedance	50	Ω
Operating Temperature Range	-40 ~ +70	°C



### MECHANICAL SPECIFICATION

SPECIFICATIONS	SPECIFICATIONS	UNIT
Antenna Dimensions	47 x 5 x 1	mm
Cable Length	100	mm
Connector	U.FL	-
Weight	5	g

#### APPROVAL

RALTRON		
DRAWN BY:	LP, March 11, 2016	
APPROVED BY:	CP, March 11, 2016	
REVISION:	A, Initial Release	

Raltron Electronics/RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort to ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.