

RPC-900-W5-GSM-MMCXRA-L250-W-G


SPECIFICATIONS

PARAMETER	VALUE
Frequency Range	GSM: 820 ~ 960 MHz
	GSM: 1710 ~ 1880 MHz
	GSM: 1850 ~ 1990 MHz
	UMTS: 1900 ~ 2170 MHz
	LTE: 2500 ~ 2700 MHz
VSWR, Max	2.1
Impedance	50 Ω
Bandwidth	140 MHz @ 900 MHz
	170 MHz @ 1800 MHz
	140 MHz @ 1900 MHz
	270 MHz @ 2000 MHz
	200 MHz @ 2600 MHz
Gain, Typical	1 dBi @ 900 MHz
	2 dBi @ 1800 MHz
	2 dBi @ 1900 MHz
	2 dBi @ 2000 MHz
	2 dBi @ 2600 MHz
Azimuth	Omni-direction
Polarization	Linear
Enclosure	PCB enclosed in Plastic Housing
Mounting	Adhesive
Cable Type	RG174
Connector Type	MMCX Right Angle Male
Cable Length – cm	250
Operating Temperature Range	-45°C to +85°C
Storage Temperature Range	-45°C to +85°C



RPC-900-W5-GSM-MMCXRA-L250-W-G

MECHANICAL SPECIFICATIONS



Cable Length L=250 ±10 cm

APPROVAL

RALTRON	
DRAWN BY	CP, March 07, 2016
APPROVED BY	CP, March 07, 2016
REVISION	A, Initial Release

Raltron Electronics/RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort to ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.