


MULTILAYER CERAMIC BAND PASS FILTER

page 1 of 3

RCF-2450.000-100000-1411-W-TR-001

Parameters		Value	Unit
Frequency		2400.000 ~2500.000	MHz
Insertion Loss, max	@ 25°C	1.05	dB
	@ -40 ~ +85°C	1.25	dB
Attenuation, min	DC ~ 960 MHz	30	dB
	960 ~ 1580 MHz	19	dB
	1710 ~ 1990 MHz	17	dB
	4800 ~ 5000 MHz	30	dB
	7200 ~ 7500 MHz	25	dB
Impedance		50	Ω
VSWR, max		2.0	-
Moisture Sensitivity Levels		LEVEL 1	-
Operating Temperature Range		-40 ~ +85	°C
Storage Temperature Range		-40 ~ +85	°C
Storage Temperature Range Before Soldering		+5 ~ +40	°C
Humidity Before Soldering		30 ~ 70	%

Dimensions



Symbol	Dimension (mm)
L	1.40 ± 0.10
W	1.10 ± 0.10
Т	0.60 max.
А	0.325 ± 0.10
В	0.25 ± 0.10
С	0.25 ± 0.10
D	0.25 ± 0.10




MULTILAYER CERAMIC BAND PASS FILTER

page 2 of 3

RCF-2450.000-100000-1411-W-TR-001


CONSTRUCTION



PIN	Connection	
1	Input port	
2	GND	
3	GND	
4	Output port	
5	GND	

Frequency Characteristics

S Parameters






MULTILAYER CERAMIC BAND PASS FILTER

page 3 of 3

RCF-2450.000-100000-1411-W-TR-001

Solder Land Pattern



Unit: mm

Line width to be designed to match 50 Ω characteristic impedance, depending on PCB material and thickness.

Raltron Electronics / RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided only for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.

Copyright © 2016, Raltron Electronics / RAMI Technology USA, LLC. All rights reserved. No part of this document may be reproduced in any form without the prior written permission of Raltron Electronics / RAMI Technology USA, LLC.

September 19, 2019