


LVDS CLOCK OSCILLATOR

Page 1 of 5


CL2520-156.250-L-20-X-T-TR-NS1

ELECTRICAL SPECIFICATION




PARAMETERS	SYMBOL	CONDITIONS	VALUE	UNIT
Nominal Frequency	f_o	$T_a=25^{\circ}\text{C}$	156.250	MHz
Supply Voltage	V_{CC}		2.375 ~ 3.63	VDC
Supply Current, max	I_s	$T_a=25^{\circ}\text{C}$	40	mA
Operating Temperature Range	T_a		-40 ~ +85	$^{\circ}\text{C}$
Storage Temperature Range	$T_{(stg)}$	Absolute max	-55 ~ +125	$^{\circ}\text{C}$
Output Logic Type			LVDS	
Overall Freq. Stability, max.	$\Delta f/f_o$	Inclusive of 25°C Tolerance, Changes due to Operating Temperature, 10 years Aging	± 20 ⇄	ppm
Output Voltage	V_{OH}	V_{OH} , max, $R_L=100\ \Omega$, $C_E \geq V_{CC}-0.3V$, OUT/OUTN	1.6	VDC
	V_{OL}	V_{OL} , min, $R_L=100\ \Omega$, $C_E \geq V_{CC}-0.3V$, OUT/OUTN	0.9	VDC
Differential Voltage, min/max	$V_{OD}/V_{OD'}$	$R_L=100\ \Omega$, $C_E \geq V_{CC}-0.3V$, OUT/OUTN	247 / 454	mV
Differential Voltage Deviation, max	ΔV_{OD}		50	mV
Offset Voltage, min/max	V_{OS}	$R_L=100\ \Omega$, $C_E \geq V_{CC}-0.3V$, OUT/OUTN	1.125 / 1.375	V
Offset Deviation, max	ΔV_{OS}		50	mV
Output Swing, min	V_{opp}		0.25	V
Output Load		Connected between Out and Complementary Out	100	Ω
Enable / Disable Function	E/D	Pin 1: N.C. (Open) or High ($0.7 \times V_{CC}$)	Pin 4 & 5 – Oscillation (Enabled)	
		Pin 1: Low ($0.3 \times V_{CC}$)	Pin 4 & 5 – High Impedance (Disabled)	
Symmetry (Duty Cycle)	DC	@50% Wave form	45 ~ 55	%
Rise Time and Fall Time, max	t_r / t_f		400	ps
Jitter, RMS, typ/max	J	@12kHz ~ 20MHz	80 / 100	fs

WAVEFORM DIAGRAM




2.5V

LVDS TYPICAL OUTPUT LEVEL




3.3V

LVDS TYPICAL OUTPUT LEVEL




■ PHASE NOISE

At 2.5V



At 3.3V




LVDS CLOCK OSCILLATOR

Page 4 of 5

CL2520-156.250-L-20-X-T-TR-NS1


MECHANICAL SPECIFICATION



Pin Connections

- 1 – Enable / Disable
- 2 – NC
- 3 – Ground
- 4 – Output
- 5 – Complimentary Output
- 6 – Vcc

CARRIER TAPE DIMENSIONS




NOTE: REFER TO EIA-481 FOR DIMENSIONS NOT LISTED

PACKAGING

- 178 mm REEL DIAMETER
- 12 mm TAPE WIDTH, 8 mm PITCH
- QUANTITY: 3000 PIECES PER REEL

REFLOW PROFILE



Reflow profile		
Temperature Min Preheat	T _{SMIN}	150°C
Temperature Max Preheat	T _{SMAX}	200°C
Time (T _{SMIN} to T _{SMAX})	t _S	60-180 sec.
Temperature	T _L	217°C
Peak Temperature	T _P	260°C
Ramp-up rate	R _{UP}	3°C/sec max.
Ramp-down rate	R _{DOWN}	6°C/sec max.
Time within 5°C of Peak Temperature	t _P	10 sec.
Time t[25°C] to Peak Temperature	t[25°C] to Peak	480 sec.
Time	t _L	60-150 sec.

ENVIRONMENTAL

PARAMETER	VALUE
MOISTURE SENSITIVITY LEVEL	1
RoHS	Compliant
REACH-SVHC	Compliant
HALOGEN-FREE	Compliant
TERMINATION FINISH	Au



MARKING

Rx156.25

•LDEyw

x – 1 or 2 Digits as Internal Production ID code

y – Year code

w – Week code

YEAR CODE	
Year	Code
2018	8
2019	9
2020	0
2021	1
2022	2
2023	3
2024	4
2025	5
2026	6
2027	7
2028	8
2029	9

ALPHA WEEK CODE TABLE					
Week	Code	Week	Code	Week	Code
1	a	19	s	37	K
2	b	20	t	38	L
3	c	21	u	39	M
4	d	22	v	40	N
5	e	23	w	41	O
6	f	24	x	42	P
7	g	25	y	43	Q
8	h	26	z	44	R
9	i	27	A	45	S
10	j	28	B	46	T
11	k	29	C	47	U
12	l	30	D	48	V
13	m	31	E	49	W
14	n	32	F	50	X
15	o	33	G	51	Y
16	p	34	H	52	Z
17	q	35	I		
18	r	36	J		

APPROVAL

RALTRON	
DRAWN BY:	CP, December 04, 2019
APPROVED BY:	Jl, December 04, 2019
REVISION:	A, Initial Release B CP, April 17, 2020, Updated the Current Revision Levels C, AR, August 28, 2020, Updated Waveform Diagram D, Tape/reel quantity revised to 3K pieces 7/12/22 KJ E, Updated to current spec levels by XLiu, October 21, 2022

Raltron Electronics/RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort to ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.

Copyright © 2016, Raltron Electronics / RAMI Technology USA, LLC. All rights reserved. No part of this document may be reproduced in any form without the prior written permission of Raltron Electronics / RAMI Technology USA, LLC.