



#### ELECTRICAL SPECIFICATION

PARAMETER	SYMBOL	CONDITIONS	VALUE	UNIT
Nominal Frequency	$f_o$	Ta=25°C	156.250	MHz
Oscillation Mode			Fundamental	-
Supply Voltage	V <sub>CC</sub>	V <sub>CC</sub> ±10%	3.3	VDC
Supply Current, typ/max	I <sub>S</sub>	V <sub>CC</sub> ; Ta=+25°C;	40 / 60	mA
Operating Temperature Range	T <sub>a</sub>	---	-40 ~ +105	°C
Storage Temperature Range	T <sub>(stg)</sub>	Absolute max	-55 ~ +125	°C
Output Logic Type	---		LVPECL	
Freq. Stability, max.	$\Delta f/f_o$	Inclusive of 25°C Tolerance and Changes due to Operating Temperature, Supply Voltage, Load Variation and Aging	±50	ppm
Output Voltage	V <sub>OH</sub>	Logic "1" Level, min	V <sub>CC</sub> -1.075	VDC
	V <sub>OL</sub>	Logic "0" Level, max	V <sub>CC</sub> -1.550	VDC
Output Load	---	50 Ω to V <sub>CC</sub> -2V	50	Ω
Enable / Disable Function	E/D	Pin 1: High, Pins 4 & 5 – Oscillation (Enabled), min	0.7 x V <sub>CC</sub>	V
		Pin 1: Low, Pins 4 & 5 – High Impedance (Disabled), max	0.3 x V <sub>CC</sub>	V
Symmetry (Duty Cycle)	DC	@50% V <sub>DD</sub>	45 ~ 55	%
Rise and Fall Time, typ/max	t <sub>r</sub> / t <sub>f</sub>	@20% to 80% V <sub>DD</sub>	0.25 / 0.4	ns
Standby Current, max	I <sub>st</sub>		10	μA
Start up Time, max	T <sub>start</sub>		2	ms
Jitter, RMS, typ/max @3.3V	J	1σ, 12kHz < F <sub>j</sub> < 20MHz	36.2/50	fs
Phase Noise , typ @3.3V	£ (Δf)	@ 10Hz	-72.39	dBc/Hz
		@ 100Hz	-102.20	
		@ 1KHz	-131.89	
		@ 10KHz	-152.46	
		@ 100KHz	-159.63	
		@ 1MHz	-163.83	
		@ 40MHz	-166.38	

### MECHANICAL SPECIFICATION



### CARRIER TAPE DIMENSIONS




NOTE: REFER TO EIA-481 FOR DIMENSIONS NOT LISTED


### PACKAGING

180 mm REEL DIAMETER  
8 mm TAPE WIDTH, 4 mm PITCH  
QUANTITY: 3000 PIECES PER REEL

■ PHASE NOISE GRAPH



### REFLOW PROFILE



Reflow profile		
Temperature Min Preheat	$T_{SMIN}$	150°C
Temperature Max Preheat	$T_{SMAX}$	200°C
Time ( $T_{SMIN}$ to $T_{SMAX}$ )	$t_s$	60-180 sec.
Temperature	$T_L$	217°C
Peak Temperature	$T_P$	260°C
Ramp-up rate	$R_{UP}$	3°C/sec max.
Ramp-down rate	$R_{DOWN}$	6°C/sec max.
Time within 5°C of Peak Temperature	$t_p$	10 sec.
Time $t[25^\circ\text{C}]$ to Peak Temperature	$t[25^\circ\text{C}]$ to Peak	480 sec.
Time	$t_L$	60-150 sec.

### ENVIRONMENTAL

PARAMETER	VALUE
MOISTURE SENSITIVITY LEVEL	1
RoHS	Compliant
REACH-SVHC	Compliant
HALOGEN-FREE	Compliant
TERMINATION FINISH	Au



■ MARKING

Rxx156  
•3BEyw

x – Internal Production ID code  
y – Year code  
w – Week code

YEAR CODE	
Year	Code
2019	9
2020	0
2021	1
2022	2
2023	3
2024	4
2025	5
2026	6
2027	7
2028	8
2029	9

ALPHA WEEK CODE TABLE					
Week	Code	Week	Code	Week	Code
1	a	19	s	37	K
2	b	20	t	38	L
3	c	21	u	39	M
4	d	22	v	40	N
5	e	23	w	41	O
6	f	24	x	42	P
7	g	25	y	43	Q
8	h	26	z	44	R
9	i	27	A	45	S
10	j	28	B	46	T
11	k	29	C	47	U
12	l	30	D	48	V
13	m	31	E	49	W
14	n	32	F	50	X
15	o	33	G	51	Y
16	p	34	H	52	Z
17	q	35	I		
18	r	36	J		
18	r	36	J		

■ APPROVAL

RALTRON	
DRAWN BY:	JS, February 13, 2025
APPROVED BY:	LS, February 13, 2025
REVISION:	A, Initial Release

Raltron Electronics / RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort to ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided only for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.

Copyright © 2016, Raltron Electronics / RAMI Technology USA, LLC. All rights reserved. No part of this document may be reproduced in any form without the prior written permission of Raltron Electronics / RAMI Technology USA, LLC.