


SERIES R1612



FEATURES

- ULTRA SMALL ULTRA THIN
- AUTOMATIC MOUNTING POSSIBLE
- REFLOW POSSIBLE
- EXCELLENT FOR HIGH DENSITY APPLICATIONS

SPECIFICATIONS

PARAMETER	VALUE
FREQUENCY RANGE*	24.000 MHz to 60.000 MHz
MODE OF OSCILLATION	AT CUT, Fundamental
FREQUENCY TOLERANCE AT 25°C	±50 ppm max ±10ppm, ±20ppm, ±30 ppm available
FREQUENCY STABILITY OVER TEMPERATURE*	±50 ppm max ±10ppm, ±20ppm, ±30 ppm available
OPERATING TEMPERATURE RANGE*	-10°C to +60°C Standard -40°C to +85°C Extended
STORAGE TEMPERATURE RANGE	-40°C to +85°C
AGING	±2 ppm 1st year max
LOAD CAPACITANCE	8 pF to 32 pF or Series Resonance
EQUIVALENT SERIES RESISTANCE	See Table 1
SHUNT CAPACITANCE	3.5 pF max
DRIVE LEVEL	50 µW max

*Not any Combination Frequency-Operating Temperature Range- Stability is available. Please consult factory

FREQUENCY (MHz)	MODE	MAXIMUM ESR (Ω)
24.000 to 40.999	FUND	150
41.000 to 60.000	FUND	100

PART NUMBERING SYSTEM

TYPE	-	FREQUENCY	-	LOAD CAPACITANCE	-	MODE	TOLERANCE/STABILITY (PPM/PPM)
R1612	-	IN MHz	-	8 to 32 pF for PARALLEL S for SERIES	-	Blank for < 24.576 MHz F for ≥ 24.576 MHz	Blank for MAXIMUM PPMPPM for OTHER Example: 1020, 2050


-	TEMPERATURE RANGE	-	TAPE & REEL
-	Blank for STANDARD EXT for EXTENDED	-	TR

EXAMPLE: R1612-26.000-8-F-1530-TR


Surface Mount Crystal, 1.6 x 1.2 mm, 26.000 MHz, 8 pF Load, Fundamental Mode, ±15 ppm Tolerance, ±30 ppm Stability, from -10°C to +60°C, Tape and reel Packaging

SERIES R1612

MECHANICAL SPECIFICATION



CARRIER TAPE DIMENSIONS




NOTE: REFER TO EIA-481 FOR NON-SPECIFIED DIMENSIONS

PACKAGING

180 mm REEL DIAMETER
8 mm TAPE WIDTH, 4 mm PITCH
QUANTITY: 3000 PIECES PER REEL

● REFLOW PROFILE



Reflow profile		
Temperature Min Preheat	T_{SMIN}	150°C
Temperature Max Preheat	T_{SMAX}	200°C
Time (T_{SMIN} to T_{SMAX})	t_s	60-180 sec.
Temperature	T_L	217°C
Peak Temperature	T_P	260°C
Ramp-up rate	R_{UP}	3°C/sec max.
Ramp-down rate	R_{DOWN}	6°C/sec max.
Time within 5°C of Peak Temperature	t_p	10 sec.
Time $t[25°C]$ to Peak Temperature	$t[25°C]$ to Peak	480 sec.
Time	t_L	60-150 sec.

● ENVIRONMENTAL

PARAMETER	VALUE
MOISTURE SENSITIVITY LEVEL	1
RoHS	COMPLIANT
REACH SVHC	COMPLIANT
HALOGEN-FREE	COMPLIANT
ESD CLASSIFICATION LEVEL	N/A
TERMINATION FINISH	Au



July 2020

Raltron Electronics/RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort to ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.