

Page 1 of 3

RH100-25.000-18-F-2030-EXT-TR


SPECIFICATIONS

PARAMETER	VALUE
NOMINAL FREQUENCY	25.000 MHz
MODE OF OSCILLATION	Fundamental
FREQUENCY TOLERANCE AT 25°C	±20 ppm max
FREQUENCY STABILITY OVER TEMPERATURE	±30 ppm max
OPERATING TEMPERATURE RANGE	-40°C to +85°C
STORAGE TEMPERATURE RANGE	-40°C to +85°C
AGING	±2 ppm first year max
LOAD CAPACITANCE	18 pF
EQUIVALENT SERIES RESISTANCE	60 Ω max
SHUNT CAPACITANCE	3.5 pF max
INSULATION RESISTANCE	500 MΩ min @ DC 100V
DRIVE LEVEL	300 µW max
REFLOW CONDITIONS	260°C for 10 sec max




Photo is not actual part

MECHANICAL SPECIFICATION



CARRIER TAPE DIMENSIONS



PACKAGING

178 mm REEL DIAMETER 8 mm TAPE WIDTH, 4 mm PITCH QUANTITY: 3000 PIECES PER REEL


IN ACCORDANCE WITH EIA-481



Page 2 of 3

RH100-25.000-18-F-2030-EXT-TR

• REFLOW PROFILE



Reflow profile			
Temperature Min Preheat	T _{SMIN}	150°C	
Temperature Max Preheat	T _{SMAX}	200°C	
Time (T _{SMIN} to T _{SMAX})	ts	60-180 sec.	
Temperature	TL	217°C	
Peak Temperature	T _P	260°C	
Ramp-up rate	R _{UP}	3°C/sec max.	
Ramp-down rate	R _{DOWN}	6°C/sec max.	
Time within 5°C of Peak Temperature	t _P	10 sec.	
Time t[25°C] to Peak Temperature	t[25°C] to Peak	480 sec.	
Time	tL	60-150 sec.	

ENVIRONMENTAL

PARAMETER	VALUE
MOISTURE SENSITIVITY LEVEL	1
RoHS	Compliant
REACH SVHC	Compliant
HALOGEN-FREE	Compliant
ESD CLASSIFICATION LEVEL	N/A
TERMINATION FINISH	Au





Page 3 of 3

RH100-25.000-18-F-2030-EXT-TR

MARKING

R25.000 xBDyw

- x Internal Production ID code
- y Year code w – Week code

YEAR CODE		
Year	Code	
2015	5	
2016	6	
2017	7	
2018	8	
2019	9	
2020	0	
2021	1	
2022	2	
2023	3	
2024	4	
2025	5	

	ALPHA WEEK CODE TABLE				
Week	Code	Week	Code	Week	Code
1	а	19	s	37	K
2	b	20	t	38	L
3	с	21	u	39	М
4	d	22	v	40	Ν
5	e	23	w	41	0
6	f	24	х	42	Р
7	g	25	у	43	Q
8	h	26	z	44	R
9	i	27	А	45	S
10	j	28	В	46	Т
11	k	29	С	47	U
12	1	30	D	48	V
13	m	31	E	49	W
14	n	32	F	50	Х
15	0	33	G	51	Y
16	р	34	Н	52	Z
17	q	35	I		
18	r	36	J		

APPROVAL

DRAWN BY	CP, May 26, 2015
APPROVED BY	CP, May 26, 2015
REVISION	A, Initial Release
	B, Updated to current spec levels KJ 1/29/19
	C, Updated to current spec levels XL 3/2/20
	D, Insulation resistance spec added KJ 5/14/20
	E, Drive level and mechanical specs updated KJ
	1/13/22

Raltron Electronics/RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort to ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech hos not guarantee that the information is accurate, reliable or current. The product information is provided for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not sumpare that the information is accurate, use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.

Copyright © 2016, Raltron Electronics / RAMI Technology USA, LLC. All rights reserved. No part of this document may be reproduced in any form without the prior written permission of Raltron Electronics / RAMI Technology USA, LLC.