



Items	Specification	Unit
Center frequency( $F_0$ )	173.130	MHz
Bandwidth @-3dB, typ	133	kHz
Bandwidth @-10dB, typ/max	191 / 200	kHz
Insertion Loss (within $F_0-7.5\sim F_0+30.9$ kHz) typ / max	2.6 / 3.6	dB
Ripple in Pass Band (within $F_0-7.5\sim F_0+30.9$ kHz) typ/max	0.6 / 1.0	dB
Attenuation	163.130 ~ 172.210 MHz, min/typ	-50 / -52
	174.050 ~ 183.130 MHz, min/typ	-45 / -52
Aging, max	$\pm 10$	ppm/year
Input power, max	20	dBm
DC Voltage, max	10	V
Operating Temperature	-40 to +85	$^{\circ}\text{C}$
Storage Temperature	-40 to +85	$^{\circ}\text{C}$

### Dimension



Pin Description	
A,B,C,F,G,H	Ground
I	Ground
J	Input
D	Ground
E	Output

### Frequency Characteristics



● **ENVIRONMENTAL**

PARAMETER	VALUE
MOISTURE SENSITIVITY LEVEL	1
RoHS-2	6/6 COMPLIANT & LEAD FREE
REACH SVHC	COMPLIANT
HALOGEN-FREE	COMPLIANT
ESD CLASSIFICATION LEVEL	N/A
TERMINATION FINISH	Au



● **MARKING**

173  
Rxz

x – Internal Production ID code  
z – Date Code (year / month)

DATE CODE												
	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
2015	a	b	c	d	e	f	g	h	j	k	l	m
2016	n	p	q	r	s	t	u	v	w	x	y	z
2017	A	B	C	D	E	F	G	H	J	K	L	M
2018	N	P	Q	R	S	T	U	V	W	X	Y	Z

● **APPROVAL**

DRAWN BY	CP, October 09, 2015
APPROVED BY	CP, October 09, 2015
REVISION	A, Initial Release

Raltron Electronics/RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort to ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.