



Items	Specification	Unit
Center frequency( $F_0$ )	183.600	MHz
Bandwidth	100	kHz
Insertion Loss in BW, typ/max	2.5 / 3.5	dB
Amplitude Ripple in BW, typ/max	0.5 / 1.0	dB
-1dB Bandwidth, min/typ	100 / 320	kHz
Attenuation min/typ	$F_0 \pm 400\text{kHz}$	-20 / -30
	$F_0 \pm 600\text{kHz}$	-40 / -50
	$F_0 \pm 4.140\text{kHz}$	-40 / -50
Input power, max	10	dBm
Operation Temperature	-40 to +85	°C
Storage Temperature	-45 to +85	°C

### Dimension



### Frequency Characteristics



### Environmental

PARAMETER	VALUE
MOISTURE SENSITIVITY LEVEL	1
REACH – SVHC	Compliant
RoHS 2	6/6

### ● APPROVAL

DRAWN BY	CP, November 16, 2015
APPROVED BY	CP, November 16, 2015
REVISION	A, Initial Release

Raltron Electronics/RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort to ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.