


Parameters	Specification	Unit
Center frequency(Fo)	784.000	MHz
Bandwidth (Bw)	16000	kHz
Insertion Loss (in 777~793MHz) , typ/max	1.3 / 2.0	dB
Amplitude Ripple (in 777~793MHz), typ/max	0.2 / 1.0	dB
Return Loss (in 777~793MHz), min/typ	10 / 15	-
Attenuation min/typ	DC ~ 728 MHz	-45 / -50
	728 MHz ~ 740 MHz	-40 / -45
	740 MHz ~ 757 MHz	-38 / -40
	820 MHz ~ 3000 MHz	-35 / -50
In/Out Impedance	50	$\Omega$
Input Power, max	10	dBm
Operating Temperature Range	-40 to +85	$^{\circ}\text{C}$
Storage Temperature	-40 to +85	$^{\circ}\text{C}$


Note: Specification at T=25 $^{\circ}\text{C}$

### Dimension



Pin Description	
A, C, D, F	Ground
B	In
E	Out

**Frequency Characteristics**



**Environmental**

PARAMETER	VALUE
MOISTURE SENSITIVITY LEVEL	1
REACH – SVHC	Compliant
RoHS 2	6/6

**APPROVAL**

DRAWN BY	LP, March 28, 2016
APPROVED BY	CP, March 28, 2016
REVISION	A, Initial Release

Raltron Electronics/RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort to ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.