


■ ELECTRICAL SPECIFICATION

PARAMETER		VALUE
Frequency Range (F <sub>0</sub> )		40.000 ~ 170.000 MHz
Supply Voltage (V <sub>S</sub> )		3.3 ± 10% VDC
Control Voltage Range (V <sub>CC</sub> )		1.65 ± 1.35 VDC
Input Current		35 mA max
Frequency Stability		±20 ppm, ±25, ±50 ppm, ±100 ppm
Frequency Adjustment Range		±50 ppm min, ±80 ppm min
Operating Temperature Range		-20 ~ +70°C -40 ~ +85°C
Storage temperature Range		-55 ~ +125°C
Output LVDS	Symmetry at 50% V <sub>S</sub>	40% ~ 60% Standard 45% ~ 55% Tight
	Rise / Fall Time	6 ns max
	Logic "0" Level	0.9 V max
	Logic "1" Level	1.6 V min
	Load (Terminus to V <sub>S</sub> -2V)	50 Ω
Enable / Disable Function		Pin 2: High or Open / Output enabled (Pins 4 & 5) Pin 2: Low / Output disabled (High impedance)
RMS Phase Jitter (12kHz ~ 20 MHz)		1 ps max

MECHANICAL SPECIFICATION




PART NUMBERING SYSTEM

TYPE	SERIES	VOLTAGE (V)	STABILITY (ppm)	TEMPERATURE RANGE (°C)	PULLABILITY (ppm)	SYMMETRY (%)	FREQUENCY (MHz)
VLF	3	3: 3.3	20: ±20 25: ±25 50: ±50 10: ±100	HZ: -20 ~+70 D3: -40 ~+85	50: ±50 80: ±80	blank: 40~ 60 T: 45~55	40.000 ~ 170.000

EXAMPLE: VLF3325-D3-50-T-100.000

Surface Mount VLF3 Series, LVDS Fundamental VCXO, 3.2 x 2.5 mm, 3.3 VDC Supply Voltage, ±25 ppm Stability from -40°C to +85°C, ±50 ppm Frequency Adjustment Range, Symmetry 45% to 55%, 100.000 MHz

REFLOW PROFILE



Reflow profile		
Temperature Min Preheat	$T_{SMIN}$	150°C
Temperature Max Preheat	$T_{SMAX}$	200°C
Time ( $T_{SMIN}$ to $T_{SMAX}$ )	$t_s$	60-180 sec.
Temperature	$T_L$	217°C
Peak Temperature	$T_P$	260°C
Ramp-up rate	$R_{UP}$	3°C/sec max.
Ramp-down rate	$R_{DOWN}$	6°C/sec max.
Time within 5°C of Peak Temperature	$t_p$	10 sec.
Time $t[25°C]$ to Peak Temperature	$t[25°C]$ to Peak	480 sec.
Time	$t_L$	60-150 sec.

ENVIRONMENTAL

PARAMETER	VALUE
MOISTURE SENSITIVITY LEVEL	1
REACH SVHC	COMPLIANT
RoHS	COMPLIANT
TERMINATION FINISH	Au



Raltron Electronics/RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort to ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.