


■ ELECTRICAL SPECIFICATION

PARAMETER		VALUE
Frequency Range (F_0)		60.000 ~ 200.000 MHz
Supply Voltage (V_s)		3.3 \pm 10% VDC
Oscillation Mode		Fundamental
Control Voltage Range (V_{cc})		1.65 \pm 1.65 VDC
Input Current		80 mA max
Frequency Stability		\pm 20 ppm, \pm 25 ppm, \pm 50 ppm, \pm 100 ppm
Frequency Adjustment Range		\pm 50 ppm, \pm 100 ppm min
Operating Temperature Range		-10 ~ +70°C -40 ~ +85°C
Storage Temperature Range		-55 ~ +125°C
Output LVPECL	Symmetry at 50% V_s	40% ~ 60% Standard 45% ~ 55% Tight
	Rise / Fall Time	1.0 ns max
	Logic "0" Level	1.68 V max
	Logic "1" Level	2.475V min
	Load (Terminus to V_s -2V)	50 Ω
Enable / Disable Function		Pin 1: High or Open / Output enabled (Pins 4 & 5) Pin 1: Low / Output disabled (High impedance)
RMS Phase Jitter (12kHz ~ 20 MHz)		1 ps max

MECHANICAL SPECIFICATION




PART NUMBERING SYSTEM

TYPE	SERIES	VOLTAGE (V)	STABILITY (ppm)	TEMPERATURE RANGE (°C)	PULLABILITY (ppm)	SYMMETRY (%)	FREQUENCY (MHz)
VPF	5	3: 3.3	20: ± 20 25: ± 25 50: ± 50 10: ± 100	JZ: -10 ~+70 HZ: -20 ~+70 D3: -40 ~+85	50: ± 50 100: ± 100	blank: 40~ 60 T: 45~55	60.000 ~ 200.000

EXAMPLE: VPF5325-D3-100-T-155.520

Surface Mount VPF5 Series, LVPECL Fundamental VCXO, 5.0 x 3.2 mm, 3.3 VDC Supply Voltage, ± 25 ppm Stability from -40°C to +85°C, ± 100 ppm Frequency Adjustment Range, Symmetry 45% to 55%, 155.520 MHz

REFLOW PROFILE



Reflow profile		
Temperature Min Preheat	T_{SMIN}	150°C
Temperature Max Preheat	T_{SMAX}	200°C
Time (T_{SMIN} to T_{SMAX})	t_S	60-180 sec.
Temperature	T_L	217°C
Peak Temperature	T_P	260°C
Ramp-up rate	R_{UP}	3°C/sec max.
Ramp-down rate	R_{DOWN}	6°C/sec max.
Time within 5°C of Peak Temperature	t_P	10 sec.
Time $t[25°C]$ to Peak Temperature	$t[25°C]$ to Peak	480 sec.
Time	t_L	60-150 sec.

ENVIRONMENTAL

PARAMETER	VALUE
MOISTURE SENSITIVITY LEVEL	1
REACH SVHC	COMPLIANT
RoHS	COMPLIANT
TERMINATION FINISH	Au



May 2017

Raltron Electronics/RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort to ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.