

VS9: FUNDAMENTAL LVPECL SERIES: HF VCXO, LVPECL, +3.3 VDC

DESCRIPTION: A voltage crystal controlled oscillator, high frequency, highly stable oscillator, adhering to Low Voltage Differential Signaling (LVPECL) Standards. The output can be Tri-stated to facilitate testing or combined multiple clocks. The device is contained in a sub-miniature, very low profile, leadless ceramic SMD package with 6 gold contact pads. This miniature oscillator is ideal for today's automated assembly environments.

APPLICATIONS AND FEATURES:

- ⌚ **Infiniband; Fiber Channel; SATA; 10GbE; Network Processors; SOHO Routing; SONET/SDH**
- ⌚ **Common Frequencies: 38.88 MHz; 77.76MHz; 155.52 MHz; 156.25 MHz; 161.1328 MHz;**
- ⌚ **+3.3 VDC LVPECL**
- ⌚ **Frequency Range from 1.000 to 180.000 MHz**
- ⌚ **No Multiplication is used, low phase noise and jitter**
- ⌚ **Miniature Ceramic SMD Package Available on Tape and Reel**
- ⌚ **Lead Free and ROHS Compliant**



ABSOLUTE MAXIMUM RATINGS:

PARAMETER	SYMBOL	VALUE	UNIT
Operating temperature range	Ta	-40...+85	°C
Storage temperature range	T(stg)	-55...+90	°C
Supply voltage	Vcc	+4.6	VDC
Maximum Input Voltage	Vi	Vss-0.5...Vcc+0.5	VDC
Maximum Output Voltage	Vo	Vss-0.5...Vcc+0.5	VDC

ELECTRICAL PARAMETERS:

PARAMETER	SYMBOL	TEST CONDITIONS ¹	VALUE	UNIT
Nominal Frequency	fo		1 to 180	MHz
Supply Voltage	Vcc		+3.3 ±5%	VDC
Supply Current	Is		100.0 MAX	mA
Output Logic Type			LVPECL	
Load		Connected between each output and Vcc – 2.0 VDC	50	Ω
Output Voltage Levels	Voh Vol	min max	Vcc-1.025 Vcc-1.620	VDC VDC
Duty Cycle	DC	Measured at 50% of output voltage swing	40/60 to 60/40 or 45/55 to 55/45	%
Rise / Fall Time	tr / tf	Measured at 20/80% and 80/20% output voltage swing	0.5 TYP	ns
Frequency Stability		Overall conditions	±50 ** (note 7)	ppm
Jitter	J	Integrated Phase tji RMS, Fj = 12 kHz...20 MHz	0.3 TYP**	ps
		Integrated Phase RMS tii offset frequency 50KHz to 80MHz	0.5 TYP**	ps
		Deterministic period Jitter tdj using wavecrest analyz.	0.0TYP **	ps
		Random period Jitter trj using wavecrest analyz.	2.5 TYP **	ps
		Peak to Peak Jitter Tp-p using wavecrest analyz.	25 TYP**	ps
Phase Noise typ. @155.52MHz	E(Δf) E(Δf) E(Δf) E(Δf)	Δf=10 Hz Δf=1 KHz Δf=10 KHz Δf= >=100 KHz	-65 -120 -140 -145	dBc/Hz dBc/Hz dBc/Hz dBc/Hz
Control Voltage Range	VC	Positive slope; 10% linearity MAX	0 to +3.3	VDC
Settability	Vfo		+1.65 ± 0.25	VDC
Absolute Pull Range	APR	Minimum guaranteed freq. pull over Δf/fc, over all conditions	See Part Numbering	ppm
Input Impedance	Zin		10 MIN	KΩ
Modulation Bandwidth	BW	-3 dB	10 MIN	KHz
Enable High Option; Pin 2 Output Enabled Output Disabled	En Dis	High Voltage or No Connect Ground	0.7•Vcc MIN 0.3•Vcc MAX	VDC VDC
Enable Low Option; Pin 2 Output Disabled Output Enabled	Dis En	High Voltage Ground or No Connect	0.7•Vcc MIN 0.3•Vcc MAX	VDC VDC

*1 Test Conditions Unless Stated Otherwise: Nominal Vcc, Nominal Load, +25 ±3°C

*2 Frequency Dependent

*3 May not be Available With All Temperature Ranges or Frequencies — Please Consult Factory

*4 Measured with Wavecrest SIA-3000A 10,000, Cycles no filtering

*5 Calculated from Agilent 5500 phase noise measurements

*6 Measured with Agilent 5500

*7 Tighter stabilities maybe available upon request – please consult factory


PART NUMBERING SYSTEM:


SERIES	SYMMETRY	TEMPERATURE RANGE (°C)	ABSOLUTE PULL RANGE	FREQUENCY (MHz)	Enable/Disable
VS9: UHF +3.3Vdc VCXO with LVPECL Comp. Output	A: 40/60 to 60/40% T: 45/55 to 55/45%	R: 0...+50 S: 0...+70 U: -20...+70 V: -40...+85	K: ±20 ppm L: ±25 ppm F: ±32 ppm H: ±50 ppm G: ±80 ppm J: ±100 ppm*(note 3)	1...180.000	Enable High – standard (Omit Suffix) EL; Enable Low

EXAMPLE: VS9ASH -155.520

VCXO, 7x5mm Package, +3.3 VDC Supply Voltage, LVPECL Output, Standard Symmetry, 0...+70°C Operating Temperature Range, ±50 ppm APR, 50 ppm stability, 155.520 MHz

MECHANICAL PARAMETERS:



REFLOW PROFILE:


Raltron Electronics/RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort to ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.