Frequency Components and Antennas
for
Smart Industrial Lighting
Application








Introduction



Raltron offers the most comprehensive line of frequency management components for Smart Industrial Lighting, from simple tuning fork crystals to high stability, temperature compensated crystal oscillators and antennas. These products are designed to satisfy the ultra-low power, small footprint, and low-cost requirements of this growing market.



Smart Lighting System Architecture





Solutions for Wi-Fi Protocol

The Wi-Fi/IEEE 802.11 has three frequency bands, 2.4/5/6 GHz.

Some Typical Crystal or TCXO frequencies for Wi-Fi Smart Industrial Lighting ICs:

Infineon - CYW43012 - 37.4 MHz, 32.768 kHz CY8C62xA - 16 to 35 MHz , 32.768 kHz

Silicon Labs - WF200 - 38.4 MHz, 32.768 kHz RS9116 - 40 MHz, 32.768 kHz

Microchip - ATWINC3400A-MU - 26 MHz, 32.768 kHz

Raltron Stub Antennas Solutions

RST-2400-P-190-IPEX-H RST-MB-P-153-SMA-G





The Wi-Fi 6/IEEE 802.11ax has two frequency bands, 2.4/5 GHz.

The Crystals for lower frequencies of Wi-Fi 6 such as 38.4 and 48 MHz, and for higher are 76.8 and 96 MHz

Some Typical Crystals or TCXO frequencies for Wi-Fi 6 Smart Industrial Lighting ICs:

SparkLan - WNFB-266AXI(BT) - 37.4 MHz, 32.768 kHz AP6281 - 59.97 MHz, 32.768 kHz

See All Crystal Products

See Antenna Products for Wi-Fi



Solutions for Bluetooth & BLE Protocol

Bluetooth Low Energy uses the same 2.4 GHz radio frequencies as classic Bluetooth Some Typical Crystal or TCXO frequencies for Bluetooth & BLE Smart Industrial Lighting ICs:

Infineon - PSoC 6 MCU: CY8C63x6, CY8C63x7 - 16 MHz/32 MHz Crystal Oscillator
16 to 35 MHz, 32.768 kHz On-chip Crystal Oscillators
- 2.4 GHz Chip Antenna


Nordic Semiconductor - nRF52810 - 64 MHz Crystal Oscillator, 32 MHz Crystal 32.768 kHz Crystal Oscillator, 32.768 kHz Crystal 1 MHz/16 MHz/32 MHz Peripheral Clock - 2.4 GHz Antenna

Texas Instruments - CC2640R2F - 32.8 kHz/48 MHz RC Oscillator, 24 MHz Crystal Oscillator 32.768 kHz Crystal Oscillator - 2.4 GHz Antenna

NXP Semiconductors - MKW39/38/37 - 26 MHz/32 MHz Crystal, 32.768 kHz Crystal Oscillator - 2.4 GHz Antenna

Dialog Semiconductor - DA1469x - 32 MHz Crystal, 32.768 kHz Crystal Oscillator - 2.4 GHz Antenna

STMicroelectronics - BlueNRG-LPS - 32 MHz Crystal, 32.768 kHz Crystal - 2.4 GHz Antenna



See All Crystal Products
See Antenna Products for Bluetooth



Solutions for ZigBee Protocol

The ZigBee/IEEE 802.15.4 has three frequency bands, allowing operation in all regions of the world: 2.4 GHz for worldwide applications, 868 MHz for Europe and 915 MHz for the American.

Some Typical Crystal or TCXO frequencies for ZigBee Smart Industrial Lighting ICs:

Texas Instruments - CC2652RSIP - 48 MHz Crystal

48 MHz Crystal Oscillator 32.768 kHz Crystal Oscillator

- 2.4 GHz Inverted F Antenna

Nordic Semiconductor - nRF52832 - 64 MHz Crystal Oscillator 32 MHz Crystal, 32.768 kHz Crystal Oscillator - 2.4 GHz Chip Antenna

NVD Considerations INFARO 22 MHz Constal Consillators

NXP Semiconductors - JN5189 - 32 MHz Crystal Oscillator 32.768 kHz Crystal Oscillator - 2.4 GHz Antenna

Raltron Stub Antennas Solutions

RST-2400-P-190-IPEX-H RST-MB-P-153-SMA-G



See All Crystal Products
See Antenna Products for ZigBee



Raltron Solutions - MHz Crystals

Available Crystal Packages

Part #	Size(mm)
R2016-32.000-12-F-1010-EXT-TR	1.60 x 1.25 x 0.32
R2016-48.000-8-F-1030-EXT-TR	2.00 x 1.60 x 0.50
R2520-16.000-10-1020-EXT-TR	2.50 x 2.00 x 0.65
RH100-24.000-9-1010-TR	3.20 x 2.50 x 0.70

See All Crystal Products

Typical Frequencies:

16 MHz, 26 MHz, 32 MHz, 37.4 MHz, 38.4 MHz, 48 MHz, 59.97 MHz , 64 MHz

Stock at our Distributors

Product Series	Datasheet	Image	Contact Us / Buy Now
R1612 View products in stock	PDF		Buy Now
R2016 View products in stock	PDF		Buy Now
R2520 View products in stock	PDF		Buy Now
RH100 View products in stock	PDF		Buy Now















Raltron Solutions - Tuning Fork 32.768 kHz

Available Tuning Fork Crystal Packages

Part #	SIZE(mm)
RT1210-32.768-9-TR	1.2 x 1.0
RT1610-32.768-12.5-TR	1.6 x 1.0
RT2012-32.768-7-20-EXT-TR	2.0 x 1.2
RT3215-32.768-12.5-TR	3.2 x 1.5
RSE-32.768-12.5-H14-TR	6.9 x 1.4
RSM200S-32.768-12.5-TR	8.0 x 3.8

Load capacitance values: 6 pF, 7 pF, 9 pF and 12.5 pF

Frequency Tolerances: ±20 ppm and ±10 ppm









Stock at our Distributors

Product Series	Datasheet	Image	Contact Us / Buy Now
RT1210 View products in stock	PDF		Buy Now
RT1610 View products in stock	PDF		Buy Now
RT2012 View products in stock	PDF		Buy Now
RT3215 View products in stock	PDF		Buy Now
RSE H14	PDF		Buy Now
RSM200S View products in stock	PDF		Buy Now

See All Crystal Products



Raltron Solutions - TCXO s and VCTCXOs

Raltron TCXOs IC Solutions

Part #	Size(mm)
RTX-1612BD32-S-52.000-TR	1.6 x 1.2
RTX-2016AD333-S-26.000-TR	2.0 x 1.6
RTX-2520AD31-S-26.000-TR	2.5 x 2.0
RTX-2520AF32-S-48.000-TR	2.5 x 2.0

See All TCXOs Products

- Tighter Stability: ±0.5 ppm ~ ±2.5 ppm, -40 ~ +85°C
- Improved Frequency Tuning Characteristic
- Superior Phase Noise Performance (-130 dBc/Hz on the floor)
- Range Supply Voltage: 1.8 V ~ 3.3 V
- Typical Frequencies: 10.0 MHz, 16.0 MHz, 19.2 MHz, 20.0 MHz, 26.0 MHz, 32.0 MHz, 38.4MHz, 48.0 MHz, 50.0 MHz, 52.0 MHz

Stock at our Distributors

Product Series	Datasheet	Image	Contact Us / Buy Now
RTX-1612 View products in stock	PDF	4	Buy Now
RTX /RTV-2016 View products in stock	PDF	•	Buy Now
RTX /RTV-2520 View products in stock	PDF		Buy Now

















Raltron Solutions – Antennas

Raltron Antennas Solutions

Part #	Datasheet	Image	Frequency(MHz)	Contact Us / Buy Now
RCA-3216-A1-TR	PDF	•	2450±50	Contact Us
RCA-5220-A0-TR	PDF		2450±50	Buy Now
RCA-E-3216-A2-TR	PDF		2400~2483.5	Contact Us
RCA-E-3216-E1-TR	PDF	-	1575	Contact Us
RCA-W2-P-3216-A29-G	PDF		2545	Contact Us
RCA-W2A1-3216-Z-040	PDF		2400~2500	Buy Now

<u>See Antenna Products for Wi-Fi</u> <u>See Antenna Products for Bluetooth</u> <u>See Antenna Products for ZigBee</u>













Raltron Solutions – SAW Filters


Raltron SAW Filter IC Solutions

Part #	Datasheet	Size(mm)	Contact Us / Buy Now
RSF-1176.450-20460-1109-TR	PDF	1.1 x 0.9 x 0.55	Buy Now
RSF-1582.400-46800-1109-TR	PDF	1.1 x 0.9 x 0.55	Buy Now
RSF-915.000-926000-2016-TR	PDF	2.0 x 1.6 x 0.73	Contact Us



















See All SAW Filters Products



Raltron Solutions - RF Connectors

Raltron RF connectors with low insertion loss and excellent voltage standing wave ratio support the high-level performance demanded by Smart Industrial Lighting.

Product #	Datasheet	Image	Connector Family	Description
RCN-3F-3108-K-001	PDF		BNC	BNC Straight Jack PCB Receptacle
RCN-4F-28012-K-001	PDF	á	MCX	MCX Straight Jack PCB Receptacle
RCN-5F-33106-K-001	PDF	977	MMCX	MMCX Straight Jack PCB Receptacle
RCN-17M-12816-K-001	PDF	O.K.	<u>N</u>	Type N Right Angle Plug
RCN-1M-21419-K-001	PDF	6	<u>SMA</u>	SMA Straight Plug (Quick Fit) for Semi Rigid Cable
RCN-9F-16801-K-001	PDF	Carlot Carlot	TNC	TNC Straight Jack Bulkhead Crimp





Raltron Solutions - RF Cable Assemblies

Raltron cable assemblies range from simple jumpers to power and high-speed data cables.

Product #	Datasheet	Image	Cable Assemblies	Description
RCB-16-F-95-11-SD	PDF	>	SMA to IPEX	RP SMA Jack S/T For RF1.13 Cable
RCB-21-174-150-DO-001	PDF	11	MCX to MCX	MCX Plug to MCX R/A Plug For RG174 Cable
RCB-14-H-100-12-SD	PDF	1	MCX to SMA	SMA Jack to MCX Plug For RF1.37 Cable
RCB-15-A-100-12-SD	PDF	♦	MMCX to SMA	SMA to MMCX For RG174 Cable
RCB-13-J-600-13-SD	PDF	TE,	TNC to SMA	TNC Jack S/T For RG316 Cable











CABLE ASSEMBLIES SHORT FORM CATALOG



Contact

http://www.raltron.com

Raltron Electronics

10400 N.W. 33rd Street

Miami, FL 33172, U.S.A.

Phone: 305 593 6033

Fax: 305 594 3973

