

ELECTRICAL SPECIFICATION

PARAMETERS		VALUE		UNIT
Frequency Range		698 ~ 960	1710 ~ 2700	MHz
Gain		3	4	dBi
VSWR, max		2.0		-
Radiation		Omni-Direction		-
Horizontal Beam width		360		°
Vertical Beam width		35		°
Polarization		Vertical		-
Lightning Protection		DC Grounded		-
Input Power, max		100		W
Impedance		50		Ω
Cable	Type	RG58U		-
	Length	5000		mm
Connector		SMA Male		-
Antenna Radome Material		Fiberglass		-
Mounting Way		Wall Mount		-
Diameter of Installation Pole		Ø30 ~ Ø50		mm
Dimensions		Ø20x200		mm
Weight, max		186		g
Rated Wind Velocity		60		m/s
Operating Temperature Range		-40 ~ +70		°C
RoHS Compliant		YES		-



Raltron Electronics / RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided only for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.

Copyright © 2016, Raltron Electronics / RAMI Technology USA, LLC. All rights reserved. No part of this document may be reproduced in any form without the prior written permission of Raltron Electronics / RAMI Technology USA, LLC.

May, 2020