





### Electrical Specifications

Parameters		Value	Unit
Center Frequency (Fo)		2442.000	MHz
Insertion Loss, typ/max	@ 2402.500 ~ 2421.500 MHz	1.8 / 2.2	dB
	@ 2407.500 ~ 2426.500 MHz	1.6 / 1.9	dB
	@ 2412.500 ~ 2471.500 MHz	1.5 / 1.8	dB
	@ 2457.500 ~ 2476.500 MHz	1.6 / 1.9	dB
	@ 2462.500 ~ 2481.500 MHz	1.8 / 2.2	dB
Amplitude Ripple, typ/max (p-p)	@ 2402.500 ~ 2481.500 MHz	0.8 / 1.5	dB
VSWR, typ/max	@ 2402.500 ~ 2481.500 MHz	1.7 / 2.1	dB
Attenuation, min/typ	@ 925.000 ~ 960.000 MHz	-30 / -35	dB
	@ 1559.000 ~ 1606.000 MHz	-30 / -33	dB
	@ 2110.000 ~ 2170.000 MHz	-30 / -34	dB
	@ 2300.000 ~ 2370.000 MHz	-44 / -48	dB
	@ 2505.000 ~ 2570.000 MHz	-37 / -42	dB
	@ 2570.000 ~ 2620.000 MHz	-32 / -36	dB
	@ 2620.000 ~ 2690.000 MHz	-30 / -34	dB
	@ 4800.000 ~ 5000.000 MHz	-35 / -45	dB
@ 7200.000 ~ 7500.000 MHz	-27 / -30	dB	
DC Voltage VDC		5	V
Input Power, max	@ 5000h, 50°C	25	dBm
ESD Voltage Sensitive Discharge Device	ESD(MM):	50	VDC
	ESD(HBM):	175	VDC
Operating Temperature Range		-30 ~ +85	°C
Storage Temperature Range		-40 ~ +85	°C
Moisture Sensitivity Level		MSL 2	-



### Dimension




### Test Circuit



### Frequency Characteristics



### Tape Dimension



### Environmental

PARAMETER	VALUE
REACH – SVHC	Compliant
RoHS	Compliant
PACKAGING	TAPE & REEL



### APPROVAL

DRAWN BY	AR, May 29, 2020
APPROVED BY	CP, May 29, 2020
REVISION	A, Initial Release

Raltron Electronics / RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided only for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.

Copyright © 2016, Raltron Electronics / RAMI Technology USA, LLC. All rights reserved. No part of this document may be reproduced in any form without the prior written permission of Raltron Electronics / RAMI Technology USA, LLC.