





#### ELECTRICAL SPECIFICATION


PARAMETER		VALUE	UNIT
Frequency Range		2400 ~ 2500   5100 ~ 5900	MHz
Gain	@ 2.4 GHz	4 ±0.5	dBi
	@ 5 GHz	6 ±0.5	dBi
VSWR, max		1.5	-
H Plane BW		360	°
E Plane BW	@ 2.4 GHz	50 ±1	°
	@ 5 GHz	15 ±1	°
Polarization		Vertical	-
Input Power, max		50	W
Impedance		50	Ω
Connector		N Male	-
Radome Material		UV ABS	-
Lightning Protection		DC Grounded	-
Dimensions		∅22 x 200	mm
Weight		100	g
IP Rating		IP67	-
Humidity	No Condensation	95	%
Operating Temperature Range		-40 ~ +70	°C

#### FREQUENCY CHARACTERISTICS





E-Plane (5GHz)



Raltron Electronics / RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided only for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.

Copyright © 2016, Raltron Electronics / RAMI Technology USA, LLC. All rights reserved. No part of this document may be reproduced in any form without the prior written permission of Raltron Electronics / RAMI Technology USA, LLC.

December 2020